

Wi-Fi6 802.11ax Indoor Dual band Wireless AP

Introduction



VAP7660H is an 802.11 ax dual-band wireless enterprise-level access point (2.4GHz 2*2 ax and 5GHz 2*2 ax). The rate can reach 1.774Gbps. By seamlessly working with ABLOOMY local AC (CAM), ABLOOMY private cloud (CSP) and ABLOOMY public cloud (ACS), it can build all kinds of customized, enterprise-grade wireless networks through an approach which combines simplicity, scalability, extensibility, reliability, performance and security. It is suitable for small and medium-sized enterprises, commercial environments such as airport stations, stadiums, cafes, leisure centers.

Highlights

Wi-Fi 6(802.11ax)

Supports 1024QAM modulation and 2x2MIMO, the data rate of the 5GHz air interface is up to 1.2Gbps, and the whole device data rate is 1.774Gbps. The support of OFDMA scheduling enables multiple users to receive and send data at the same time, reducing delay and improving performance.

Load Balancing and Band Steering

Supports load balancing based on the number of access users, traffic, and frequency bands, and the system automatically guides users to the 5GHz frequency band by default, which maximizes network capacity and ensures the best access experience for users.

Zero Touch Provision

Fully supports plug-and-play deployment. No matter the network environment is complex or not, whether the device is deployed in the public or private network, as long as the device can access the AC, the system can automatically complete the configuration and the network is up running without manual intervention.

Easy Maintenance

Supports real-time monitoring and alarms based on AP system status, and sending alarms automatically when detecting faults; supports automatic software update in batch mode based on policies of AP location, model, version, and the update time.

Network Security

Supports L4 stateful firewall, role-based NAC (Network Access Control), white/black lists, URL logging, and full 802.11i security standard.

Auto Power and Auto Channel

Supports automatic TX power adjustment to automatically detect and compensate the signal coverage; supports automatic/manual adjustment of channels to ensure that the AP is in the best radio frequency environment and provide users with the best QOS.

Hardware Specifications

- VAP7660H ceiling-mounted AP, adopts Qualcomm's latest 802.11ax chip IPQ60XX solution, and can work in both 2.4GHz and 5GHz frequency bands at the same time. The theoretical wireless rate reaches 573.5Mbps (2.4GHz) + 1221Mbps (5GHz) throughput.
- VAP7660H is designed with a full built-in antenna and provides two gigabit interfaces.
- VAP7660H adopts PoE power supply, and can also be powered by an external 12V DC power supply. More detailed specifications are as follows:

CPU	Qualcomm IPQ60XX
Memory	DDR3 1GB 32MB SPI Flash, 256MB NAND Flash
RF	2.4GHz:802.11ax 2.4GHz 2x2 5GHz :802.11ax 5GHz 2x2
Port	1x 10/100/1000/2500 Base TX MDI/MDIX RJ 45 port with PoE 802.3af/at 1 × 10/100/1000 Base TX MDI/MDIX RJ 45 port 1 DC Jack, 12V/1A 1 Reset pin hole
LED Description	5× LED (Power, LAN1, LAN2, 2.4G,5G)
Power Supply	12 V DC (Not included) Support PoE 802.11af/at
Working Environment	Temperature: 0° C to +40° C Humidity: 5% to 95% non-condensing
Antenna	Frequency: 2.4GHz ✓ Max Gain: ≥4 dBi Frequency: 5.15~5.85GHz ✓ Max Gain: ≥5 dBi
Max Tx Power	2.4G: 19dBm 5GHz: 20dBm
Physical Dimension	145mm(H) × 145mm(W) × 36mm(D)
Installation	Adopt a disc-shaped mounting piece, one piece is fixed on the roof, one piece

	is fixed on the AP, and the two pieces are twist and lock together.
--	---

Software Specifications

WLAN Feature	Comply with IEEE801.11a/b/g/n/ac/ax standard
	Support dynamic rate adjustment
	Support 1024QAM modulation
	Support 802.11ax standard
	Support automatic channel scanning and manual selection
	Support dynamic power adjustment and manual power adjustment
	Support fast roaming protocol (802.11r 802.11k)
	Support Short GI in 20M, 40M, 80M mode
	Support OFDMA scheduling
	Support WMM
	Support band steering
	Support load balancing based on AP traffic, frequency band and number of users
Security Feature	Support Open-system authentication method
	Support WEP authentication/encryption method
	Support WPA/WPA2-PSK authentication/encryption method
	Support WPA/WPA2-802.1X authentication/encryption method
	Support WPA-WPA2 hybrid authentication method
	Support WPA3-Personal authentication/encryption method
	Support WPA3-802.1x authentication/encryption method
	Support WPAI authentication/encryption method
Support 802.1X, Mac, portal, SMS + non-perceptual authentication methods	
Network Feature	Support local forwarding and centralized forwarding data traffic
	Support user access isolation under the same SSID
	Support role-based NAC (Network Access Control) and ACL
	Support bandwidth control based on each user
	Support data rate limit based on WAN port bandwidth
	Support network detection based on Ping and Arp
	Support switching AP to standalone mode when the connection between AP and AC is lost to make sure the data traffic is not interrupted
	Support AC active/standby deployment
	Support DHCP Server
	Support static IP/DHCP/PPOE
	Support IPV6 function
	Support VLAN pooling
	Support Soft-GRE function
Support VPDN (Virtual Private Dialup Network) function	
Management & Maintenance	Support AP and AC deployed in the cross-Internet mode
	Support Web UI management (HTTPS)
	Support CLI-based management

	Support SSH-based management
	Support updating AP's login credential remotely
	Support Zero Touch Provisioning
	Support LED light control
	Support scheduled restart of AP
	Support batch modification of AP's AC access address
	Support software update in the batch mode based on the policies of AP location, model, version and update time