

VAP6056B Outdoor Access Point



Designed with enterprise-grade requirements in mind, VAP6056B is a low cost single-band 802.11n access point supporting 2x2:2 MIMO and a data rate of up to 300Mbps. VAP6056B has one of the lowest costs of any available outdoor access point. The access point complies with the requirements of IP66 and lightning protection. They can seamlessly work with ABLOOMY local AC (CAM), ABLOOMY private cloud (CSP) and ABLOOMY public cloud (ACS). Leveraging a purpose-built edge-computing architecture, ABLOOMY access points build all kinds of customized, enterprise-grade wireless networks through an approach which combines simplicity, scalability, extensibility, reliability, performance and security.

Features

Plug-and-Play

With zero configurations, ABLOOMY access points can be activated and up-and-running in seconds.

Self-optimizing

The Tx power can be adjusted automatically based on the RF environment to achieve the best wireless coverage; the automatic radio channel adjustment ensures that the AP is running on the best radio channel to reduce RF interference and congestion.

Load Balancing

Supports load balancing based on users and traffic.

Network functions

Support NAT, Firewall, QoS and other network gateway functions.

Security

Advanced security features, such as WPA2-AES, 802.1X, firewall, role-based access control, rogue AP detection and user isolation, help to create enterprise secure wireless networks.

Guest networks

Provides isolated internet-only access for visitor. Enforces customized network access control policies.

Traffic shaping

Controls bandwidth usage based on ports, users and vlan.

Data analytics

Collects and visualizes the data from both the network and the physical world, providing visibility regarding network status and visitor statistics.

Location Based Service

Tracks client location with a patented algorithm based on Wi-Fi RF fingerprint, providing the client with proper localized services.

Automatic Maintenance

By monitoring the network status in real time, the AP system will create alerts, providing the knowledge for rapid troubleshooting. It also supports batch upgrading based on AP locations, models, versions, and other similar information. Upgrades can be scheduled autonomously, allowing for automatic network maintenance.

Specifications

Models	VAP6056B
Dimensions	170mm*137mm*55mm
Weight	300g
Interface	1*10/100M adaptive WAN port
Antenna	2*integrated directional antenna 2.4G antenna gain≥10dBi;
MIMO Streams	2.4GHz: 2x2
Max Data Rates	300Mbps
Power Supply	24V passive PoE
Standards	IEEE802.11a/b/g/n
Power consumption	6W(max)
Max Tx Power	2.4G : 23dBm
Frequency	IEEE802.11b/g/n:2.4000GHz~2.4835GHz ;
Channel	America/Canada:1-11, Europe (ETSI X30) :1-13, Japan X41:1-13
Adjustment	802.11b:BPSK,QPSK,CCK ; 802.11a/g/n:BPSK,QPSK,16-QAM,64-QAM
Protection Degree	IP66
Operating Temperature	-40°C~65°C
Operating Humidity	0%~90% non-condensing
Load Balance	Support the load balance based on AP traffic and users
Probe	Support
QOS	Support bandwidth control based on users, role, time, location, etc.
Forwarding Mode	Support local forwarding and Central forwarding
IPV6	Support
Soft GRE	Support
User Management	Support Web, CLI, SSH user management
Alerts	Support AP status alerts
RF	Auto and manual channel adjustment Adjustable power output Support seamless roaming
AP access	Broadcast discovery DHCP Option 43 DNS domain discovery Access across Internet and VPN remotely
Security	802.1X authentication Facebook authentication Google authentication SMS authentication Senseless authentication No authentication White and black list User isolation

	Wireless intrusion detection Detect and prevent rogue AP Role-based user rule Bandwidth control
Access control	IP-based filtering MAC-based filtering Protocol-based filtering Port-based filtering
Statistics	Statistics of access history Statistics of locations Network state, the online time of AP and users
Protocol	PPPoE, static IP, DHCP DHCP Server NAT DNS agency
Wireless optimization	Limit low-speed client connection Limit number of SSID clients connection
Configuration management	Support Web, CLI, SSH user management